



CONNECTION THAT POWERS INDIA



LIST OF PRODUCTS COVERED IN OUR HDC LP

- Aluminium Armoured /
Unarmoured Cables
- Copper Armoured /
Unarmoured Cables
- HT Cables
- Instrumentation Cables
- Rubber Cables
- JFTC Unarmoured/Armoured Cables
& Dry Telephone Armoured
- RS 485 Cables
- Fire Survival Cables
- Fire Survival Aluminium Cables
- Optical Fibre Cables



POLYCAB INDIA LIMITED

Aluminium Armoured Cables

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm, 4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098 (Part 1) 1988

Aluminium Armoured					
(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		87	97		112
4		95	109		126
6		112	130		149
10		136	164		175
16	91	154	167		208
25	119	180	225	252	272
35	141	223	293	314	356
50	173	276	384	409	459
70	222	368	487	549	602
95	233	472	618	688	753
120	290	562	735	855	926
150	341	680	916	998	1112
185	417	820	1117	1258	1414
240	515	1066	1407	1610	1773
300	633	1299	1710	1937	2191
400	797	1593	2258	2473	2842
500	1029	2107	2823	3357	3694
630	1202	2652	3745	4561	4996
800	1583				
1000	2005				

EXTRA FOR SPECIAL CONSTRUCTION	
a) Round Wire Armouring	
- 2 x 16 & above	25%
- 3 x 16 & 3.5CX25 & above	25%
- 4 x 10 & above	25%
- For Single core 95 & above	25%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	5%
Extruded PVC Innersheath 70 & Above	2.5%
d) HR PVC Insulation	10%
e) HR PVC Inner Sheath	5%
f) HR PVC Outer Sheath	5%
g) Oxygen Index (FR)	2.5%
h) PVC Insulated Cables	8%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
Power (Al.)				
Upto 16	10%	7.5%	15%	20%
25 - 50	7.5%	7.5%	12.5%	15%
70 & above	5%	5.0%	15%	12.5%
Power Single Core (Al.)				
Upto 16	-N.A-	10%	-N.A-	25%
25 - 50	-N.A-	10%	-N.A-	20%
70 & above	-N.A-	7.5%	-N.A-	17.5%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INDIA LIMITED

Aluminium Unarmoured Cables

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098 (Part 1) 1988

Aluminium Unarmoured					
(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		55	70		82
6		69	88		103
10		97	119		132
16	50	98	132		166
25	78	142	195	236	251
35	95	196	266	286	319
50	124	239	334	375	413
70	165	328	452	515	570
95	206	407	570	646	695
120	253	495	696	827	822
150	304	594	861	976	1041
185	373	716	1052	1226	1296
240	428	952	1342	1490	1688
300	534	1163	1615	1884	2014
400	668	1447	2064	2398	2726
500	924	1759	2690	3237	3496
630	1100	2240	3601	4381	4785
800	1478				
1000	1905				

EXTRA FOR SPECIAL CONSTRUCTION	
a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	5%
Extruded PVC Innersheath 70 & Above	2.5%
c) HR PVC Insulation	10%
d) HR PVC Inner Sheath	5%
e) HR PVC Outer Sheath	5%
f) Oxygen Index (FR)	2.5%
g) PVC Insulated Cables	8%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
	Power (Al.)			
Upto 16	10%	7.5%	15%	20%
25 - 50	7.5%	7.5%	12.5%	15%
70 & above	5%	5%	15%	12.5%
	Power Single Core (Al.)			
Upto 16	-N.A.-	10%	-N.A.-	25%
25 - 50	-N.A.-	10%	-N.A.-	20%
70 & above	-N.A.-	7.5%	-N.A.-	17.5%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INDIA LIMITED

Copper Armoured Cables

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured							
(Rate in Rs. Per Mtr.)							
Cable Size in Sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		206	272	357	440	516	595
6		284	380	517	614	736	838
10		413	583	775	956		
16	394	613	860	1146	1453		

Control Cables (Rate in Rs. Per Mtr.)						
Number of Cores	2XWY/2XFY			Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.			1.5 Sq.mm.	2.5 Sq.mm.
2	114	152		14	470	703
3	145	199		16	511	823
4	176	249		19	601	937
5	213	298		24	749	1178
6	239	354		27	819	1291
7	265	400		30	893	1488
8	307	459		37	1089	1818
10	352	518		44	1322	2246
12	410	609		61	1805	3062

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES)	
A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.50%
D) Round Wire Armouring	
1C x 95 sq. mm & above	7.50%
1.5 sq.mm - 12 core & above	15%
2.5 sq.mm - 9 core & above	15%
10 sq.mm - 4 core & above	15%
16 sq.mm - 2 core & above	15%
16 sq.mm - 3 core & above	15%
E) OXYGEN INDEX (FR)	2.50%
F) HR PVC Insulatoin	7%
HR I/S & O/S	5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	7.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
H) PVC Insulated Cables	5%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
Armoured				
2 to 4 Core	5%	6%	15%	15%
5 to 10 Core	5%	4%	15%	15%
12 & Above	5%	4%	12.50%	12.50%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INDIA LIMITED

Copper Unarmoured Cables

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured					
(Rate in Rs. Per Mtr.)					
Cable Size in Sq.mm	1 Core	2 Core	3 Core	4 Core	
	2XY	2XY	2XY	2XY	
4		175	245	311	
6		251	351	451	
10		398	564	702	
16	330	561	824	1069	
Control Cables (Rate in Rs. Per Mtr.)					
Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	84	118	14	389	668
3	111	166	16	453	790
4	141	218	19	538	904
5	175	267	24	678	1145
6	197	304	27	737	1243
7	226	363	30	855	1381
8	270	418	37	1033	1702
10	319	470	44	1219	2043
12	349	581	61	1719	2786

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES)	
A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.5%
D OXYGEN INDEX (FR)	2.5%
E) HR PVC Insulation	7%
HR PVC I/S & O/S	5% Each
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	7.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
G) PVC Insulated Cables	5%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
Unarmd				
2 - 4	5%	6%	15%	15%
5 - 10	5%	4%	15%	15%
12 & Above	5%	4%	12.5%	12.5%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INDIA LIMITED

Copper Armoured / Unarmoured Cables

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured						
(Rate in Rs. Per Mtr.)						
Cable Size in Sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XW _a Y / 2XF _a Y	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	581	877	1342	1611	1765	2273
35	781	1376	1903	2166	2504	3398
50	1073	1858	2596	3029	3439	4662
70	1492	2592	3748	4370	5073	
95	1924	3460	4964	5724	6653	
120	2410	4249	6189	7412	8285	
150	3009	5315	7732	9420	10179	
185	3650	6525	9818	11442	12947	
240	4706	8501	12632	14595	16489	
300	5953	10783	16136	18219	21211	
400	7954	14610	21223	24481	27815	
500	9766					
630	12277					
800	15540					
1000	19534					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured					
(Rate in Rs. Per Mtr.)					
Cable Size in Sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core
	2XY	2XY	2XY	2XY	2XY
25	506	849	1268	1415	1658
35	686	1308	1780	2043	2375
50	960	1788	2442	2901	3215
70	1344	2396	3556	4204	4854
95	1837	3265	4861	5696	6427
120	2320	4114	5786	7293	7921
150	2908	5143	7401	9088	9969
185	3573	6292	9249	10814	12879
240	4654	8147	12148	14104	16328
300	5863	10166	15269	17312	20187
400	7677	13515	19490	22504	26051
500	9701				
630	12212				
800	15469				
1000	19338				

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES)	
A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	2.50%
D) Round Wire Armouring	
1C x 95 sq. mm & above	7.50%
10 sq.mm - 4 core & above	15%
16 sq.mm - 2 core & above	15%
16 sq.mm - 3 core & above	15%
E) OXYGEN INDEX (FR)	2.50%
F) HR PVC Insulatoin	7%
HR I/S & O/S	5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	4%
H) PVC Insulated Cables	5%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

• The above rates are exclusive of GST which shall be charged extra. • This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INDIA LIMITED

HT Cables

“POLYCAB” Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables						
(Rate in Rs. Per Mtr.)						
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		708				
50		810				
70	926	951				
95	1058	1125	1455	1513	2017	
120	1269	1302	1689	1727	2302	
150	1412	1447	1867	1904	2437	2895
185	1644	1686	2088	2134	2690	3205
240	1973	2023	2456	2501	3078	3633
300	2346	2406	2823	2870	3457	4052
400	2902	2956	3406	3493	4003	4661

EXTRA FOR SPECIAL CONSTRUCTION:	
1) Extruded PVC Inner Sheath	3%
2) Pressure Extruded PVC Innersheath	13%
3) Round Wire Armouring - Up to 11 KV (E)	25%
11 KV (UE) & Above	27.5%
4) FRLS PVC Inner Sheath	5%
5) FRLS PVC Outer Sheath	5%
6) FR Sheath with Oxygen Index	3%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INDIA LIMITED

HT Cables

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable confirming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables						
(Rate in Rs. Per Mtr.)						
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	698	732	767	805	891	938
300	812	857	894	943	1005	1057
400	986	1039	1070	1126	1190	1252
500	1252	1319	1298	1364	1488	1564
630	1505	1586	1546	1627	1766	1856
800	1853	1948	1878	1975	2060	2169
1000	2222	2339	2440	2571	2683	2821

Size in Sq.mm.	22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	915	961	1068	1125	1309	1379
300	1027	1082	1252	1319	1443	1520
400	1217	1280	1432	1505	1652	1738
500	1488	1564	1757	1850	1905	2008
630	1766	1856	2059	2167	2232	2348
800	2060	2169	2358	2482	2683	2821
1000	2683	2821	2876	3017	3080	3242

EXTRA FOR SPECIAL CONSTRUCTION:	
1) FRLS PVC Inner Sheath	7.5%
2) FRLS PVC Outer Sheath	5%
3) Oxygen Index	3%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INDIA LIMITED

Instrumentation Cables

Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire) Round/Strip Armoured PVC Outer Sheathed Instrumentation

OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES											
Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	100	0.75	116	1	129	1.5	155	2.5	213
CORE	3	0.5	115	0.75	138	1	156	1.5	194	2.5	269
CORE	4	0.5	133	0.75	159	1	186	1.5	237	2.5	336
CORE	5	0.5	148	0.75	183	1	215	1.5	277	2.5	401
CORE	6	0.5	167	0.75	207	1	247	1.5	317	2.5	468
CORE	7	0.5	177	0.75	226	1	269	1.5	349	2.5	519
CORE	8	0.5	199	0.75	253	1	304	1.5	398	2.5	589
CORE	10	0.5	234	0.75	299	1	363	1.5	478	2.5	718
CORE	12	0.5	261	0.75	339	1	414	1.5	551	2.5	812
CORE	14	0.5	296	0.75	379	1	465	1.5	627	2.5	941
CORE	16	0.5	323	0.75	422	1	521	1.5	704	2.5	1048
CORE	19	0.5	363	0.75	482	1	600	1.5	806	2.5	1236
CORE	24	0.5	439	0.75	591	1	720	1.5	994	2.5	1537
PAIR	1	0.5	100	0.75	116	1	129	1.5	155	2.5	213
PAIR	2	0.5	145	0.75	175	1	199	1.5	250	2.5	355
PAIR	3	0.5	175	0.75	214	1	253	1.5	326	2.5	476
PAIR	4	0.5	204	0.75	258	1	310	1.5	403	2.5	600
PAIR	5	0.5	240	0.75	304	1	366	1.5	484	2.5	718
PAIR	6	0.5	272	0.75	349	1	425	1.5	564	2.5	844
PAIR	7	0.5	296	0.75	385	1	473	1.5	634	2.5	942
PAIR	8	0.5	333	0.75	435	1	535	1.5	713	2.5	1065
PAIR	10	0.5	398	0.75	516	1	643	1.5	869	2.5	1310
PAIR	12	0.5	449	0.75	597	1	747	1.5	1016	2.5	1536
PAIR	14	0.5	489	0.75	670	1	847	1.5	1164	2.5	1559
PAIR	16	0.5	554	0.75	753	1	951	1.5	1234	2.5	2003
PAIR	19	0.5	629	0.75	871	1	1107	1.5	1524	2.5	2342
PAIR	24	0.5	783	0.75	1086	1	1376	1.5	1914	2.5	2943
TRIAD	1	0.5	116	0.75	139	1	157	1.5	195	2.5	270
TRIAD	2	0.5	191	0.75	237	1	263	1.5	341	2.5	492
TRIAD	3	0.5	237	0.75	299	1	343	1.5	449	2.5	665
TRIAD	4	0.5	284	0.75	367	1	427	1.5	564	2.5	837
TRIAD	5	0.5	328	0.75	435	1	507	1.5	683	2.5	1017
TRIAD	6	0.5	378	0.75	504	1	593	1.5	789	2.5	1196
TRIAD	7	0.5	417	0.75	558	1	664	1.5	889	2.5	1361
TRIAD	8	0.5	470	0.75	615	1	744	1.5	1009	2.5	1553
TRIAD	10	0.5	557	0.75	760	1	902	1.5	1242	2.5	1915
TRIAD	12	0.5	634	0.75	875	1	1056	1.5	1450	2.5	2267
TRIAD	14	0.5	720	0.75	1000	1	1210	1.5	1666	2.5	2610
TRIAD	16	0.5	799	0.75	1114	1	1358	1.5	1887	2.5	2959
TRIAD	19	0.5	923	0.75	1293	1	1582	1.5	2206	2.5	3471
TRIAD	24	0.5	1143	0.75	1618	1	1979	1.5	2777	2.5	4368
QUAD	1	0.5	139	0.75	166	1	190	1.5	240	2.5	335

POLYCAB INDIA LIMITED

Instrumentation Cables

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Drain Wire PVC Inner Sheathed Unrmoured PVC Outer Sheathed Instrumentation Cable.

OVERALL SHIELDED - UNARMoured INSTRUMENTATION CABLES											
Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	1	0.5	59	0.75	72	1	85	1.5	102	2.5	141
PAIR	2	0.5	95	0.75	117	1	141	1.5	199	2.5	270
PAIR	3	0.5	123	0.75	157	1	199	1.5	257	2.5	385
PAIR	4	0.5	141	0.75	199	1	257	1.5	328	2.5	499
PAIR	5	0.5	186	0.75	244	1	358	1.5	398	2.5	616
PAIR	6	0.5	213	0.75	270	1	385	1.5	485	2.5	726
PAIR	7	0.5	229	0.75	312	1	398	1.5	541	2.5	841
PAIR	8	0.5	257	0.75	344	1	471	1.5	616	2.5	957
PAIR	10	0.5	312	0.75	444	1	570	1.5	771	2.5	1196
PAIR	12	0.5	374	0.75	511	1	672	1.5	913	2.5	1409
PAIR	14	0.5	413	0.75	587	1	771	1.5	1041	2.5	1623
PAIR	16	0.5	485	0.75	654	1	884	1.5	1196	2.5	1852
PAIR	19	0.5	556	0.75	783	1	1026	1.5	1396	2.5	2179
PAIR	24	0.5	685	0.75	969	1	1280	1.5	1754	2.5	2763
TRIAD	1	0.5	80	0.75	89	1	114	1.5	139	2.5	204
TRIAD	2	0.5	131	0.75	161	1	200	1.5	258	2.5	383
TRIAD	3	0.5	175	0.75	214	1	272	1.5	358	2.5	542
TRIAD	4	0.5	216	0.75	269	1	349	1.5	459	2.5	708
TRIAD	5	0.5	260	0.75	326	1	426	1.5	564	2.5	879
TRIAD	6	0.5	304	0.75	385	1	501	1.5	672	2.5	1042
TRIAD	7	0.5	344	0.75	435	1	571	1.5	768	2.5	1198
TRIAD	8	0.5	389	0.75	498	1	651	1.5	884	2.5	1366
TRIAD	10	0.5	477	0.75	614	1	815	1.5	1094	2.5	1699
TRIAD	12	0.5	556	0.75	726	1	958	1.5	1292	2.5	2015
TRIAD	14	0.5	636	0.75	835	1	1104	1.5	1492	2.5	2333
TRIAD	16	0.5	728	0.75	946	1	1253	1.5	1699	2.5	2665
TRIAD	19	0.5	849	0.75	1106	1	1470	1.5	1994	2.5	3143
TRIAD	24	0.5	1061	0.75	1388	1	1845	1.5	2526	2.5	3958
QUAD	1	0.5	85	0.75	108	1	137	1.5	186	2.5	270

POLYCAB INDIA LIMITED

Instrumentation Cables

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES											
Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	199	0.75	217	1	249	1.5	304	2.5	417
PAIR	3	0.5	245	0.75	273	1	318	1.5	393	2.5	553
PAIR	4	0.5	292	0.75	333	1	389	1.5	492	2.5	684
PAIR	5	0.5	342	0.75	392	1	465	1.5	571	2.5	826
PAIR	6	0.5	390	0.75	457	1	541	1.5	676	2.5	968
PAIR	7	0.5	430	0.75	504	1	601	1.5	759	2.5	1094
PAIR	8	0.5	489	0.75	556	1	672	1.5	860	2.5	1249
PAIR	10	0.5	578	0.75	680	1	819	1.5	1052	2.5	1532
PAIR	12	0.5	658	0.75	780	1	946	1.5	1230	2.5	1805
PAIR	14	0.5	748	0.75	889	1	1084	1.5	1402	2.5	2073
PAIR	16	0.5	840	0.75	1002	1	1218	1.5	1581	2.5	2346
PAIR	19	0.5	960	0.75	1150	1	1407	1.5	1846	2.5	2741
PAIR	24	0.5	1196	0.75	1446	1	1768	1.5	2328	2.5	3449
TRIAD	2	0.5	234	0.75	270	1	305	1.5	381	2.5	524
TRIAD	3	0.5	292	0.75	346	1	399	1.5	506	2.5	717
TRIAD	4	0.5	356	0.75	428	1	496	1.5	621	2.5	912
TRIAD	5	0.5	418	0.75	507	1	594	1.5	758	2.5	1118
TRIAD	6	0.5	484	0.75	578	1	683	1.5	888	2.5	1313
TRIAD	7	0.5	535	0.75	645	1	766	1.5	1005	2.5	1491
TRIAD	8	0.5	598	0.75	741	1	870	1.5	1148	2.5	1702
TRIAD	10	0.5	718	0.75	895	1	1065	1.5	1408	2.5	2115
TRIAD	12	0.5	832	0.75	1041	1	1245	1.5	1645	2.5	2479
TRIAD	14	0.5	938	0.75	1183	1	1429	1.5	1898	2.5	2854
TRIAD	16	0.5	1054	0.75	1333	1	1603	1.5	2148	2.5	3240
TRIAD	19	0.5	1221	0.75	1549	1	1881	1.5	2525	2.5	3796
TRIAD	24	0.5	1532	0.75	1949	1	2373	1.5	3154	2.5	4804

POLYCAB INDIA LIMITED

Instrumentation Cables

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

INDIVIDUAL & OVERALL SHIELDED - UNARMoured INSTRUMENTATION CABLES											
Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	123	0.75	141	1	174	1.5	213	2.5	300
PAIR	3	0.5	157	0.75	199	1	244	1.5	300	2.5	429
PAIR	4	0.5	199	0.75	244	1	300	1.5	385	2.5	556
PAIR	5	0.5	244	0.75	300	1	374	1.5	471	2.5	685
PAIR	6	0.5	286	0.75	358	1	444	1.5	556	2.5	815
PAIR	7	0.5	328	0.75	398	1	499	1.5	627	2.5	927
PAIR	8	0.5	374	0.75	456	1	570	1.5	726	2.5	1069
PAIR	10	0.5	456	0.75	570	1	713	1.5	899	2.5	1310
PAIR	12	0.5	530	0.75	672	1	827	1.5	1051	2.5	1567
PAIR	14	0.5	627	0.75	771	1	969	1.5	1224	2.5	1809
PAIR	16	0.5	700	0.75	871	1	1085	1.5	1396	2.5	2065
PAIR	19	0.5	815	0.75	1026	1	1280	1.5	1638	2.5	2438
PAIR	24	0.5	1026	0.75	1280	1	1611	1.5	2065	2.5	3064
TRIAD	2	0.5	169	0.75	190	1	232	1.5	292	2.5	421
TRIAD	3	0.5	225	0.75	260	1	320	1.5	406	2.5	596
TRIAD	4	0.5	284	0.75	333	1	413	1.5	528	2.5	783
TRIAD	5	0.5	344	0.75	403	1	501	1.5	643	2.5	962
TRIAD	6	0.5	399	0.75	475	1	594	1.5	773	2.5	1143
TRIAD	7	0.5	453	0.75	541	1	680	1.5	884	2.5	1313
TRIAD	8	0.5	515	0.75	625	1	783	1.5	1008	2.5	1499
TRIAD	10	0.5	643	0.75	770	1	965	1.5	1249	2.5	1873
TRIAD	12	0.5	755	0.75	903	1	1138	1.5	1473	2.5	2223
TRIAD	14	0.5	866	0.75	1041	1	1313	1.5	1704	2.5	2574
TRIAD	16	0.5	976	0.75	1180	1	1490	1.5	1936	2.5	2925
TRIAD	19	0.5	1143	0.75	1382	1	1751	1.5	2292	2.5	3424
TRIAD	24	0.5	1431	0.75	1748	1	2215	1.5	2882	2.5	4338

POLYCAB INDIA LIMITED

Rubber Cables

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)									
Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						384	557	774	1100
2 Core	100	159	226	340	576	858	1284	1740	2478
3 Core	140	220	315	471	805	1217	1821	2483	3536
4 Core	181	287	412	624	1052	1595	2380	3257	4689
5 Core	223	348							
6 Core	261	406							
7 Core	292	462							
8 Core	340	568							
10 Core	448	702							
12 Core	527	825							
14 Core	607	952							
16 Core	690	1077							
19 Core	805	1264							
24 Core	1024	1609							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)									
Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	1545	2027	2572	3199	3898	5151	6451	8470	
3 Core	4978	6526	8233	10246	12487	16427	20603	26955	
4 Core	6544	8595	10859	13515	16483	21678	27160	35644	



Connection Zindagi Ka

POLYCAB INDIA LIMITED

Jelly Filled Telephone Cables and Dry Telephone Cables

Polycab brand Jelly Filled Telephone Cables, solid annealed copper, polythene insulated, petroleum jelly filled with poly-al laminate moisture barrier, polythene sheathed, unarmoured polythene jacketed telephone cables as per dot/ polycab specification

Rate/Mtr.						
SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	72	119	207	468	900	1750

Polycab brand jelly filled telephone cables, solid annealed copper, polythene insulated, petroleum jelly filled with poly-al laminate moisture barrier, polythene sheathed, g.S.Tape armoured polythene jacketed telephone cables as per dot/ polycab specification

Rate/Mtr.						
SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	127	183	279	559	1007	1917

Polycab brand, Solid Copper conductor, Polythene Insulation, Twisted pairs, lay-up, Ext ST1 Grey PVC Inner sheath, Single layer GS Round wire armoured, Ext ST1 Grey PVC Outer sheathed Telephone Armoured Cable as per BSNL GR/WIR-06/03 Mar 2002

TELEPHONE ARMoured CABLES				
SIZE	2 PAIR	5 PAIR	10 PAIR	20 PAIR
0.5	91	141	207	274

POLYCAB INDIA LIMITED

RS 485 Cables (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	117
	22 AWG	0.32	128
	20 AWG	0.50	137
	18 AWG	0.80	161
	17 AWG	1.00	174
2 Pair	24 AWG	0.205	171
	22 AWG	0.32	185
	20 AWG	0.50	204
	18 AWG	0.80	253
	17 AWG	1.00	280

RS 485 Cables (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	70
	22 AWG	0.32	77
	20 AWG	0.50	84
	18 AWG	0.80	106
	17 AWG	1.00	120
2 Pair	24 AWG	0.205	109
	22 AWG	0.32	123
	20 AWG	0.50	139
	18 AWG	0.80	180
	17 AWG	1.00	204

POLYCAB INDIA LIMITED

RS 485 Cables (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	128
	22 AWG	0.32	141
	20 AWG	0.50	150
	18 AWG	0.80	176
	17 AWG	1.00	192
2 Pair	24 AWG	0.205	188
	22 AWG	0.32	204
	20 AWG	0.50	224
	18 AWG	0.80	278
	17 AWG	1.00	309

RS 485 Cables (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	78
	22 AWG	0.32	84
	20 AWG	0.50	92
	18 AWG	0.80	117
	17 AWG	1.00	131
2 Pair	24 AWG	0.205	120
	22 AWG	0.32	135
	20 AWG	0.50	152
	18 AWG	0.80	197
	17 AWG	1.00	224

POLYCAB INDIA LIMITED

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/XLPE Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	251	313		381
2.5	313	400		494
4	368	482		603
6	476	637		806
10	673	921		1177
16	893	1246		1640
25	1273	1834	2208	2410
35	1694	2457	2840	3243
50	2232	3263	3826	4320
70	3103	4558	5333	6036
95	4078	6004	7013	7957
120	5074	7502	8939	9962
150	6213	9200	10629	12207
185	7676	11377	13318	15093
240	9759	14495	16941	19249
300	12090	17961	20961	23874
400	15738	23413	27135	31123



Connection Zindagi Ka

POLYCAB INDIA LIMITED

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	280	344		417
2.5	344	434		530
4	401	516		642
6	510	674		847
10	714	962		1224
16	931	1286		1693
25	1321	1886	2266	2470
35	1745	2515	2903	3311
50	2290	3327	3897	4401
70	3174	4641	5423	6133
95	4159	6093	7112	8064
120	5160	7600	9057	10089
150	6316	9320	10764	12357
185	7791	11519	13479	15268
240	9898	14667	17133	19461
300	12254	18161	21185	24129
400	15943	23668	27422	31437

POLYCAB INDIA LIMITED

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	291	360		436
2.5	356	450		553
4	413	533		665
6	524	695		875
10	729	986		1256
16	949	1316		1730
25	1351	1932	2321	2531
35	1780	2565	2964	3379
50	2334	3394	3977	4489
70	3231	4726	5525	6248
95	4222	6188	7228	8190
120	5236	7715	9201	10244
150	6414	9469	10941	12557
185	7919	11711	13700	15521
240	10050	14897	17403	19766
300	12434	18431	21505	24489
400	16169	24005	27825	31887



Connection Zindagi Ka

POLYCAB INDIA LIMITED

Fire Survival Aluminium Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Armoured/FRLS Sheathed FS Aluminium Power Cables

(Rate/Mtr.)		
Sq.mm.	3 Core	4 Core
16	445	575
25	600	764
35	726	937
50	898	1164
70	1227	1597
95	1534	1996
120	1833	2402
150	2181	2857
185	2643	3452
240	3290	4302
300	3959	5196
400	4927	6453

POLYCAB INDIA LIMITED

Optical Fibre Uni-Tube Un-Armoured Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/XLpe Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Cable Type	Fiber Type	Rate. Per Km.
2F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	23500
4F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	27250
6F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	30750
8F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	37500
12F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	43750
6F UNI-TUBE OPTICAL FIBRE CABLES	Multimode	55000
12F UNI-TUBE OPTICAL FIBRE CABLES	Multimode	93500

Optical Fibre Uni-Tube Armoured Cables

Cable Type	Fiber Type	Rate. Per Km.
24F UNI-TUBE OPTICAL FIBRE CABLES	Multimode	175500



Connection Zindagi Ka

Regional & Branch Offices:

EAST

GUWAHATI : 3rd Floor, Purbi Complex, Near Panbazar Flyover, A. T. Road, Guwahati - 781001.

KOLKATA : Unit No-1108, 11th Floor, Godrej Genesis, Plot-XI, Block EP & GP Salt Lake, Sector - V, Kolkata - 700091.

ORISSA : A-167, Unit No.102, First Floor, The Metropolis, Near Sparsh Hospital, Saheed Nagar, Bhubaneswar-751007, Odisha Tel. 0674 2549960

PATNA : L-302, 303 Dumraon Palace, 3rd Floor, Fraser Road, Near Dakbangla Crossing, Patna - 800001.

NORTH

CHANDIGARH : S.C.O. 10-11-12, 1st Floor, Sec 17 B, Chandigarh - 160017. Tel. 0172 5001548,49

LUCKNOW : Shalimar Square, Office No - 09, 126/31, B. N. Road, Lalbagh, Hazratganj, Lucknow -226001. Tel. 0522 4022324

NOIDA : B9, 1st Floor Sector - 3, Near Bajaj Bhawan, Noida - 201301. Tel. 0120 4848550

DEHRADUN : 57 GDG Tower Adjoining Hotel Calista Patel Nagar Dehradun, Uttrakhand - 248001, Tel. 0135 2728758

WEST

AHMEDABAD : 102-1st Floor, Hrishikesh, Nr. IDBI Bank Cross Road, Gulbai Tekra, Ahmedabad - 380006. Tel. 079 26301655

INDORE : B-12, New Siyaganj, Patthar Godam Road, Indore - 452003. Tel. 0731 4033357

PUNE : Off No. 36, Sangam Project Phase 2, Near RTO Pune, Near Sangam Bridge, Pune - 411001. Tel. 020 26058277

RAIPUR : 506, 5th Floor, Wallfort Ozone, Near Fafadih Chowk, Raipur - 492001. Tel. 0771 2582925, 4221686

SOUTH

BENGALURU : B-78, No.18, 4th Main Road, KSSIDC Industrial Estate, 6th Block, Rajajinagar, Bangalore - 560010. Tel. 080 23102172 / 8354

CHENNAI : Gee Gee Universal, 8th Floor, No.2, Mc Nichols Road, 3rd Lane, Near Metha Hospital Chetpet, Chennai - 600 031, Phone. 044-42817272

SECUNDERABAD : 208-209, 2nd Floor Bhuvana Towers S. D. Road, Secunderabad - 500 003. Tel. 040 66326228

KOCHI : 34/138 C, NH By-Pass Road, Edappally, Kochi - 682024. Tel. 0484 2803285

Corporate Office:

POLYCAB INDIA LIMITED (formerly known as 'Polycab Wires Limited')

Polycab House, 771, Mogul Lane, Mahim (W), Mumbai - 400 016, Maharashtra (India)

Ph.: +91-22-2432 7070/4, 6735 1400, Email: enquiry@polycab.com, Toll Free No.: 1800 267 0008